

UNICLEAN GP EXTRA

DESCRIPTION

- No petroleum solvents, non-flammable.
- Biodegradable, non-toxic, wastewater will split into an oil/water phase.
- Fresh smell.
- Strong degreasing properties when diluted.
- Leaves no film residues on cleaned surfaces.
- Suitable on most common metals and coatings.
- Suitable for use with oil-water separators.

APPLICATIONS

UNICLEAN GP/HCF is used for engine rooms, decks, bulkheads and accommodation.

DIRECTIONS FOR USE

FOR HEAVY CONTAMINATION

UNICLEAN GP/HCF is applied by spray undiluted and left for 20-60 minutes. It must then be hosed off with a powerful waterjet, whilst brushing the surfaces.

GENERAL CLEANING

UNICLEAN GP/HCF can be diluted to a 2% solution in water for light cleaning. It must be allowed to soak for 1-15 minutes before rinsing with a waterjet. Using water at a temperature of 20°C up to 60°C for dilution and rinsing increases the effectiveness of the product.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is not subjected to any recommendation. Voluntary UNIMARINE recommendation:

- S2 : Keep out of reach of children
S24/25 : Avoid contact with skin and eyes

No. 4.15



UNICLEAN GP EXTRA

Water based
general purpose degreaser

- Environmentally friendly product
- Alternative for: Cold Wash, Marisol, Genepol, Water Based Neutral HCF (ex BTS)

PRODUCT CHARACTERISTICS

Appearance:	clear liquid with a fresh citrus odor
pH 1% solution:	10
Specific gravity:	0,985c (20°C)
Flash point:	none to boiling (100°C)
IMO Class:	not regulated
UN Number:	not regulated
ADR:	not regulated

UNiclean